

Hot-Dip Galvanized Threaded Rods

A **valmont**  COMPANY



Features: Available in cut lengths, or 6' sections.

Construction: SAE J429 (Latest Revision) Grade 2 Stud, Rolled or Cut UNC Threads. Coarse threads

Design Criteria: Conforms to the minimum requirements as stated in SAE J429 (Latest Revision) Grade 2 Stud, Rolled or Cut CNC threads. SAE J429 Grade 2 (Yield Fy = 57 ksi / Tensile Fu = 74 ksi). All finished goods are Hot Dip Galvanized in accordance with ASTM A123 requirements.

Part #	Diameter	Length	Weight
G38R-12	3/8"	12"	0.3 lb.
G38R-72	3/8"	72"	1.8 lb.
G12R-6	1/2"	6"	0.25 lb.
G12R-8	1/2"	8"	0.35 lb.
G12R-10	1/2"	10"	0.45 lb.
G12R-12	1/2"	12"	0.50 lb.
G12R-20	1/2"	20"	0.90 lb.
G12R-24	1/2"	24"	1.10 lb.
G12R-72	1/2"	72"	3.20 lb.
G58R-8	5/8"	8"	0.55 lb.
G58R-10	5/8"	10"	0.70 lb.
G58R-12	5/8"	12"	0.85 lb.
G58R-14	5/8"	14"	1.00 lb.
G58R-18	5/8"	18"	1.30 lb.
G58R-24	5/8"	24"	1.70 lb.
G58R-48	5/8"	48"	3.45 lb.
G58R-72	5/8"	72"	5.20 lb.
G34R-72	3/4"	72"	7.45 lb.