



| PARTS LIST | | | | | | |
|------------|-----|----------|--------------------------------------|-----------|-------------|---------|
| ITEM | QTY | PART NO. | PART DESCRIPTION | LENGTH | UNIT WT. | NET WT. |
| 1 | 6 | X-LWRM | RING MOUNT WELDMENT | | 68.81 | 412.85 |
| 2 | 3 | P472 | 4-1/2" X 72" SCH. 40 GALVANIZED PIPE | 72 in | 64.89 | 194.68 |
| 3 | 12 | X-214130 | BENT PLATE V-CLAMP | 12 5/8 in | 11.43 | 137.16 |
| 4 | 24 | G58R-14 | 5/8" x 14" THREADED ROD (HDG.) | | 0.40 | 9.57 |
| 5 | 18 | G58R-48 | 5/8" x 48" THREADED ROD (HDG.) | | 0.40 | 7.18 |
| 6 | 18 | G58R-24 | 5/8" x 24" THREADED ROD (HDG.) | | 0.40 | 7.18 |
| 7 | 36 | A58FW | 5/8" HDG A325 FLATWASHER | | 0.03 | 1.22 |
| 8 | 144 | G58LW | 5/8" HDG LOCKWASHER | | 0.03 | 3.76 |
| 9 | 144 | A58NUT | 5/8" HDG A325 HEX NUT | | 0.13 | 18.70 |
| 10 | 12 | X-178627 | BENT EXTENSION BRACKET | 15 in | 15.80 | 189.58 |
| 11 | 36 | A5802 | 5/8" x 2" HDG A325 HEX BOLT | | 0.27 | 9.78 |
| | | | | | TOTAL WT. # | 991.66 |

TOLERANCE NOTES

TOLERANCES ON DIMENSIONS, UNLESS OTHERWISE NOTED ARE:
 SAWED, SHEARED AND GAS CUT EDGES ($\pm 0.030"$)
 DRILLED AND GAS CUT HOLES ($\pm 0.030"$) - NO CONING OF HOLES
 LASER CUT EDGES AND HOLES ($\pm 0.010"$) - NO CONING OF HOLES
 BENDS ARE $\pm 1/2$ DEGREE
 ALL OTHER MACHINING ($\pm 0.030"$)
 ALL OTHER ASSEMBLY ($\pm 0.060"$)

PROPRIETARY NOTE:
 THE DATA AND TECHNIQUES CONTAINED IN THIS DRAWING ARE PROPRIETARY INFORMATION OF VALMONT INDUSTRIES AND CONSIDERED A TRADE SECRET. ANY USE OR DISCLOSURE WITHOUT THE CONSENT OF VALMONT INDUSTRIES IS STRICTLY PROHIBITED.

DESCRIPTION
LARGE MONOPOLE SECTOR FRAME ATTACHMENT ASSEMBLY

| | | |
|---------|---------------|---------------|
| CPD NO. | DRAWN BY | ENG. APPROVAL |
| | KC8 3/18/2016 | 3RD PARTY |
| CLASS | DRAWING USAGE | CHECKED BY |
| 81 | CUSTOMER | BMC 5/10/2016 |



Engineering
 Support Team:
 1-888-753-7446

Locations:
 New York, NY
 Atlanta, GA
 Los Angeles, CA
 Plymouth, IN
 Salem, OR
 Dallas, TX

| | |
|----------|---------|
| PART NO. | MSFAA-L |
| DWG. NO. | MSFAA-L |