

## Pxxx: Bulk Pipe



### Features:

- Factory cut end, hot-dip galvanized pipe

### Construction:

- ASTM A53 Grade B
- Schedule 40

### Design Criteria:

- ASTM A53 Grade B (Yield Fy = 35 ksi [240 MPa] / Tensile Fu = 60 ksi [415 MPa])
- Hot dip galvanized in accordance with ASTM A123 requirements

Part #	Length	OD x Length (in)	Weight
P263	5'-3"	2-3/8" x 63"	20 lb
P272	6'-0"	2-3/8" x 72"	22 lb
P284	7'-0"	2-3/8" x 84"	26 lb
P296	8'-0"	2-3/8" x 96"	30 lb
P2120	10'-0"	2-3/8" x 120"	37 lb
P2126	10'-6"	2-3/8" x 126"	39 lb
P2150	12'-6"	2-3/8" x 150"	46 lb
P2174	14'-6"	2-3/8" x 174"	53 lb
P3084	7'-0"	2-7/8" x 84"	41 lb
P3096	8'-0"	2-7/8" x 96"	47 lb
P30120	10'-0"	2-7/8" x 120"	58 lb
P30126	10'-6"	2-7/8" x 126"	61 lb
P30150	12'-6"	2-7/8" x 150"	73 lb
P30174	14'-6"	2-7/8" x 174"	84 lb
P360	5'-0"	3-1/2" x 60"	38 lb
P372	6'-0"	3-1/2" x 72"	46 lb
P396	8'-0"	3-1/2" x 96"	61 lb
P3150	12'-6"	3-1/2" x 150"	95 lb
P3160	13'-4"	3-1/2" x 160"	101 lb
P3174	14'-6"	3-1/2" x 174"	110 lb
P3216	18'-0"	3-1/2" x 216"	137 lb
P472	6'-0"	4-1/2" x 72"	65 lb
P4126	10'-6"	4-1/2" x 126"	114 lb