



PARTS LIST						
ITEM	QTY	PART NO.	PART DESCRIPTION	LENGTH	UNIT WT.	NET WT.
1	2	ZB12	1/8" MILL PLATE (Fy=35 Ksi Min)		3.16	6.32
2	2	SS38R-30	3/8" X 30" THREADED ROD (STAINLESS STEEL)		0.94	1.88
3	4	SQW38	3/8" SQUARE WASHER	2 in	0.29	1.16
4	12	SS38NUT	3/8" SS HEX NUT		0.02	0.22
5	12	SS38LW	3/8" SS LOCKWASHER		0.01	0.08
6	12	SS38FW	3/8" STAINLESS FLATWASHER		0.01	0.11
					TOTAL WT. #	9.77

TOLERANCE NOTES

TOLERANCES ON DIMENSIONS, UNLESS OTHERWISE NOTED ARE:
 SAWED, SHEARED AND GAS CUT EDGES ($\pm 0.030"$)
 DRILLED AND GAS CUT HOLES ($\pm 0.030"$) - NO CONING OF HOLES
 LASER CUT EDGES AND HOLES ($\pm 0.010"$) - NO CONING OF HOLES
 BENDS ARE $\pm 1/2$ DEGREE
 ALL OTHER MACHINING ($\pm 0.030"$)
 ALL OTHER ASSEMBLY ($\pm 0.060"$)

PROPRIETARY NOTE:
 THE DATA AND TECHNIQUES CONTAINED IN THIS DRAWING ARE PROPRIETARY INFORMATION OF VALMONT INDUSTRIES AND CONSIDERED A TRADE SECRET. ANY USE OR DISCLOSURE WITHOUT THE CONSENT OF VALMONT INDUSTRIES IS STRICTLY PROHIBITED.

DESCRIPTION
 Z-BRACKET TRAPEZE KIT
 12" DOUBLE LEVEL



Engineering
 Support Team:
 1-888-753-7446

Locations:
 New York, NY
 Atlanta, GA
 Los Angeles, CA
 Plymouth, IN
 Salem, OR
 Dallas, TX

A valmont COMPANY

CPD NO. semb	DRAWN BY CEK 10/13/2011	ENG. APPROVAL
CLASS SUB 81 01	DRAWING USAGE CUSTOMER	CHECKED BY BMC 10/19/2011

PART NO. Z12K-D	PAGE 1 OF 1
DWG. NO. Z12K-D	