

| PARTS LIST | | | | | | |
|------------|-----|----------|---|--------|-------------|---------|
| ITEM | QTY | PART NO. | PART DESCRIPTION | LENGTH | UNIT WT. | NET WT. |
| 1 | 3 | ZB24 | Z-BRACKET WALL MOUNT FOR 8 RUNS OF COAX | | 6.00 | 18.01 |
| 2 | 2 | SS38R-36 | 3/8" X 36" THREADED ROD (STAINLESS STEEL) | | 1.13 | 2.26 |
| 3 | 4 | SQW38 | 3/8" SQUARE WASHER (GALV.) | 2 in | 0.27 | 1.09 |
| 4 | 16 | SS38NUT | 3/8" SS HEX NUT | | 0.02 | 0.29 |
| 5 | 16 | SS38LW | 3/8" SS LOCKWASHER | | 0.01 | 0.11 |
| 6 | 16 | SS38FW | 3/8" STAINLESS FLATWASHER | | 0.01 | 0.14 |
| | | | | | TOTAL WT. # | 21.90 |


| REV | DESCRIPTION OF REVISIONS | CPD | BY | DATE |
|------------------|---|-----|-----|-----------|
| A | CHANGED THREADED ROD FROM 18" LENGTH TO 36" | | CEK | 4/18/2012 |
| REVISION HISTORY | | | | |

TOLERANCE NOTES

TOLERANCES ON DIMENSIONS, UNLESS OTHERWISE NOTED ARE:
 SAWED, SHEARED AND GAS CUT EDGES ($\pm 0.030"$)
 DRILLED AND GAS CUT HOLES ($\pm 0.030"$) - NO CONING OF HOLES
 LASER CUT EDGES AND HOLES ($\pm 0.010"$) - NO CONING OF HOLES
 BENDS ARE $\pm 1/2$ DEGREE
 ALL OTHER MACHINING ($\pm 0.030"$)
 ALL OTHER ASSEMBLY ($\pm 0.060"$)

PROPRIETARY NOTE:
 THE DATA AND TECHNIQUES CONTAINED IN THIS DRAWING ARE PROPRIETARY INFORMATION OF VALMONT INDUSTRIES AND CONSIDERED A TRADE SECRET. ANY USE OR DISCLOSURE WITHOUT THE CONSENT OF VALMONT INDUSTRIES IS STRICTLY PROHIBITED.

| DESCRIPTION | |
|---|----------------|
| Z-BRACKET TRAPEZE KIT 24" TRIPLE LEVEL | |
| CPD NO. | DRAWN BY |
| 81 | CEK 10/13/2011 |
| CLASS | DRAWING USAGE |
| 01 | CUSTOMER |
| ENG. APPROVAL | CHECKED BY |
| | BMC 4/18/2012 |



A valmont COMPANY

Locations:
 New York, NY
 Atlanta, GA
 Los Angeles, CA
 Plymouth, IN
 Salem, OR
 Dallas, TX

Engineering
 Support Team:
 1-888-753-7446

| | |
|----------|--------|
| PART NO. | Z24K-3 |
| DWG. NO. | Z24K-3 |

PAGE
1 OF 1